




Dajulong No.4
复合商用卷材地板

DajuLong[®]
大巨龙弹性地板

Dajulong No.4

Dimension: 1.8mm x 2m x 20m



JL04-31




JL04-86




JL04-74




JL04-85



JL04-32




JL04-75




JL04-73




JL04-87



JL04-71



JL04-72



JL04-41




JL04-76

Dajulong No.4


规格: 1.8mm x 2m x 20m




JL04-21



JL04-83




JL04-61




JL04-80



JL04-88




JL04-84



JL04-62




JL04-81




JL04-78



JL04-51



JL04-63



JL04-82

Dajulong No.4

规格: 1.8mm x 2m x 20m



JL04-91



JL04-92



JL04-93



JL04-94

Dajulong No.4

Dimension: 1.8mm x 2m x 20m



JL04-95



JL04-96



JL04-97



JL04-98



Dajulong No.4

复合商用卷材地板



Description 规格	Standard 标准	Result 结果
Total thickness 总厚度	EN 428	1.8 mm
Wear layer thickness 耐磨层	EN 429	0.2 mm
Width 宽度	EN 426	2 m
Length of sheet 卷长	EN 426	20 m

Classification 类别

Fire rating 防火等级	GB 8624-2012	B1
Toxic testing 有害物质检测	GB 18586-2001	Good 合格
Electrical resistance 抗电阻性	EN 1081	$> 10^{9-10}$
Slip resistance dry 防干滑性	EN 13893	≥ 0.3
Slip resistance wet 防湿滑性	DIN 51130	R9

Performances 性能

Castor chair test 轮压测试	EN 425	No damage 合格
Colour fastness 颜色稳定性	EN ISO 105- B02	≥ 6
Chemical products resistance 抗化学性	EN 423	Good 好
Dimensional stability 尺寸稳定性	EN 434	$\leq 0.40\%$
Curl resultant to heat 加热翘曲	EN 434	≤ 1 mm
Sound reduction 消音率	EN ISO 717/2	Approx. 4 dB
Residual indentation 残余凹陷度	EN 433	0.03mm
Anti-bacterial and fungicidal 抗菌防霉性能		Good 好
VOC 挥发物排放量		< 10
Surface treatment 表面处理		PUR

Intertek 抗菌检测报告



FloorScore 环保检测报告



SGS 防火检测报告

